

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1. - 29. (Cancelled)

30. (Currently Amended) A transmitter for remotely controlling a locomotive in which is mounted a slave controller, said transmitter comprising:

- an interface for receiving an identifier of the slave controller via a first communication link, the first communication link being a wireless communication link;
- a data storage in communication with said interface for storing the identifier of the slave controller received via the first communication link, said data storage being operative to store an identifier of said transmitter;
- a message builder in communication with said data storage, said message builder being operative to construct a message having a tag portion and a command portion, the tag portion conveying data derived from the identifier of the slave controller and data derived from the identifier of said transmitter, ~~the command portion conveying at least one command;~~
- a message encoder in communication with said message builder to encode the message constructed by said message builder;
- a signal transmitting unit for transmitting a signal over a second communication link ~~different from the first communication link~~, the second communication link being an RF communication link, the signal being indicative of at least one command for causing an action to be performed by the locomotive.

31. (Previously Presented) A transmitter as defined in claim 30, wherein said message encoder processes the message constructed by said message builder to reduce an occurrence of consecutive 0's or 1's in the message constructed by said message builder.
32. (Previously Presented) A transmitter as defined in claim 30, wherein said signal transmitting unit is in communication with said message encoder for receiving the message encoded by said message encoder and for producing the signal conveying the at least one command on the basis of the message encoded by said message encoder.
33. (Previously Presented) A transmitter as defined in claim 32, wherein said signal transmitting unit includes a modulator for modulating the message encoded by said message encoder to produce the signal conveying the at least one command.
34. – 42. (Cancelled)
43. (Currently Amended) A transmitter for remotely controlling a locomotive, said transmitter comprising:
- a data storage for holding an identifier of said transmitter and for storing an identifier of a slave controller located on board the locomotive;
 - an interface in communication with said data storage, said interface being operative to establish a first communication link with an external entity -for transmitting to the external entity data derived from the identifier of said transmitter via the first communication link, the first communication link being a wireless communication link;
 - a message builder in communication with said data storage, said message builder being operative to construct a message having a tag portion and a command portion, the tag portion conveying data derived from the identifier of the slave controller and data derived from the identifier of said transmitter, ~~the command portion conveying at least one command~~;

- a message encoder in communication with said message builder to encode the message constructed by said message builder;
 - a signal transmitting unit in communication with said data storage, said signal transmitting unit being operative to transmit a signal to the slave controller over a second communication link ~~different from the first communication link~~, the second communication link being an RF communication link, the signal conveying:
 - a) at least one command for causing an action to be performed by the locomotive; and
 - b) data derived from the identifier of said transmitter.
44. (Previously Presented) A transmitter as defined in claim 43, wherein said signal transmitting unit is in communication with said message encoder for receiving the message encoded by said message encoder and for producing the signal conveying the at least one command on the basis of the message encoded by said message encoder.
45. (Previously Presented) A transmitter as defined in claim 44, wherein said message encoder processes the message constructed by said message builder to reduce an occurrence of consecutive 0's or 1's in the message constructed by said message builder.
46. (Previously Presented) A transmitter as defined in claim 44, wherein said signal transmitting unit includes a modulator for modulating the message encoded by said message encoder to produce the signal conveying the at least one command.
47. (Previously Presented) A transmitter as defined in claim 41, wherein said interface is operative to receive over the first communication link the identifier of the slave controller for storage in said data storage.
48. – 52. (Cancelled)
53. (Currently Amended) A slave controller for use in a locomotive having a controller module, said slave controller comprising:

- a) an interface for receiving an identifier of a transmitter via a first communication link, the first communication link being a wireless communication link;
- b) a data storage in communication with said interface, said data storage being suitable for storing the identifier of the transmitter and an identifier of said slave controller;
- c) a signal receiver unit for receiving a signal from the transmitter over a second communication link ~~different from the first communication link~~, the second communication link being an RF communication link, the signal conveying a message including a command portion indicative of at least one command for causing ~~at least one~~ an action to be performed by the locomotive, the message also including a tag portion including data derived from the identifier of the transmitter and data derived from the identifier of said slave controller;
- d) a logical processing unit in communication with said data storage and with said signal receiver unit, said logical processing unit being operative to:
 - i) perform a validation procedure on the message including comparing the tag portion in the message with the identifier of the transmitter and the identifier of said slave controller in said data storage;
 - ii) if the validation procedure validates the message, generate control signals directed to the controller module for causing the locomotive to perform the at least one action.

54. (Previously Presented) A slave controller as defined in claim 53, wherein said data storage is operative to release the identifier of said slave controller to said interface for transmission over the first communication link.

55. (Previously Presented) A slave controller as defined in claim 54, wherein the validation procedure includes an assessment of an integrity of the signal conveying a message.

56. (Previously Presented) A slave controller as defined in claim 55, wherein the assessment of the integrity of the signal conveying a message includes processing the signal conveying the message by an error detection algorithm.
57. (Previously Presented) A slave controller as defined in claim 55, wherein the assessment of the integrity of the signal conveying a message includes processing the signal conveying a message by an error correction algorithm.
58. (Cancelled)
59. (Currently Amended) A slave controller as defined in claim 53, wherein the ~~at least one~~ action to be performed by the locomotive is acceleration.
60. (Currently Amended) A slave controller as defined in claim 53, wherein the ~~at least one~~ action to be performed by the locomotive is braking.
61. (Currently Amended) In combination:
- a) a locomotive having a controller module;
 - b) a slave controller mounted on board the locomotive;
 - c) said slave controller comprising:
 - i) an interface for receiving an identifier of a transmitter via a first communication link, the first communication link being a wireless communication link;
 - ii) a data storage in communication with said interface, said data storage being suitable for storing the identifier of the transmitter and an identifier of said slave controller
 - iii) a signal receiver unit for receiving a signal from the transmitter over a second communication link ~~different from the first communication link~~, the second communication link being an RF communication link, the signal conveying a message including a command portion and a tag portion, the command portion being indicative of at least one command for causing at

~~least one~~ an action to be performed by said locomotive, the tag portion including data derived from the identifier of the transmitter and data derived from the identifier of said slave controller;

- iv) a logical processing unit in communication with said data storage and with said signal receiver unit, said logical processing unit being operative to:
 - (1) perform a validation procedure on the message including comparing data in the tag portion in the message with the identifier of the transmitter and the identifier of said slave controller in said data storage;
 - (2) if the validation procedure validates the message, generate control signals and directing the control signals to the controller module for causing said locomotive to perform the at least one action.

- 62. (Previously Presented) A combination as defined in claim 61, wherein said data storage is operative to release the identifier of said slave controller to said interface for transmission over the first communication link.
- 63. (Previously Presented) A combination as defined in claim 61, wherein the validation procedure includes an assessment of an integrity of the signal conveying a message.
- 64. (Previously Presented) A combination as defined in claim 63, wherein the assessment of the integrity of the signal conveying a message includes processing the signal conveying a message by an error detection algorithm.
- 65. (Previously Presented) A combination as defined in claim 63, wherein the assessment of the integrity of the signal conveying a message includes processing the signal conveying a message by an error correction algorithm.
- 66. (Cancelled)

67. (Currently Amended) A combination as defined in claim 61, wherein the ~~at least one~~ action to be performed by the locomotive is acceleration.
68. (Currently Amended) A combination as defined in claim 61, wherein the ~~at least one~~ action to be performed by the locomotive is braking.
69. (Currently Amended) A remote control system for a locomotive having a controller module, said remote control system comprising:
- a) a slave controller for mounting on-board the locomotive;
 - b) a transmitter for transmitting a wireless signal over a first communication link, the first communication link being an RF communication link, the wireless signal being indicative of at least one command for causing an action to be performed by the locomotive;
 - c) said slave controller being responsive to the wireless signal to generate control signals for transmission to the controller module to implement the at least one command;
 - d) said slave controller being operative to output over a second communication link, ~~different from the first communication link,~~ an identifier of said slave controller for transmission to said transmitter, the second communication link being a wireless communication link;
 - e) the wireless signal including data derived from the identifier of said slave controller.
70. (Previously Presented) A remote control system as defined in claim 69, wherein said transmitter includes a data storage for storing the identifier of said slave controller.
71. (Previously Presented) A remote control system as defined in claim 70, wherein said data storage is adapted to store an identifier of said transmitter.

72. (Previously Presented) A remote control system as defined in claim 71, wherein said transmitter includes a signal transmitting unit for transmitting the wireless signal over the first communication link.
73. (Previously Presented) A remote control system as defined in claim 72, wherein said transmitter includes a message builder in communication with said data storage, said message builder being operative to construct a message having a tag portion and a command portion, the tag portion conveying data derived from the identifier of said slave controller and data derived from the identifier of said transmitter, the command portion conveying the at least one command.
74. (Currently Amended) A remote control system as defined in claim 73, wherein said transmitter has an interface in communication with said data storage for outputting the identifier of said transmitter over ~~a communication link different from said first communication link~~ the second communication link.
75. (Previously Presented) A remote control system as defined in claim 74, wherein said interface is operative to receive the identifier of said slave controller and to transmit the identifier of said slave controller to said data storage.
76. (Previously Presented) A remote control system as defined in claim 75, wherein said interface is an IR interface.
77. (Currently Amended) A remote control system as defined in claim 76, wherein the ~~at least one~~ action to be performed by the locomotive is acceleration.
78. (Currently Amended) A remote control system as defined in claim 76, wherein the ~~at least one~~ action to be performed by the locomotive is braking.
79. (Previously Presented) A remote control system as defined in claim 69, wherein said slave controller includes:
- a) a data storage for holding the identifier of said slave controller;

- b) an interface in communication with said data storage, said interface operative to output over the second communication link via said interface the identifier of said slave controller.
80. (Previously Presented) A remote control system as defined in claim 79, wherein said interface is operative to receive over the second communication link an identifier of said transmitter and to direct the identifier of said transmitter to said data storage for storage therein.
81. (Previously Presented) A remote control system as defined in claim 80, wherein the wireless signal transmitted by said transmitter over the first communication link conveys a message including:
- a) a command portion indicative of the at least one command;
 - b) a tag portion including data derived from the identifier of said transmitter and data derived from the identifier of said slave controller.
82. (Currently Amended) A remote control system as defined in claim 81, wherein said slave controller includes a signal receiver unit for receiving the wireless signal transmitted by said transmitter over the first communication link.
83. (Currently Amended) A remote control system as defined in claim 82, wherein said slave controller includes a logical processing unit in communication with said data storage and with said signal receiver unit, said logical processing unit being operative to:
- a) perform a validation procedure on the message including comparing data in the tag portion of the message with the identifier of said transmitter and the identifier of said slave controller in said data storage;
 - b) if the validation procedure validates the message, generate control signals for transmission to the controller module for causing the locomotive to perform the at least one action.
84. (Cancelled)

85. (Currently Amended) A remote control system for a locomotive having a controller module, said remote control system comprising:
- a) a slave controller for mounting on-board the locomotive;
 - b) a transmitter for transmitting a wireless signal over a first communication link, the first communication link being an RF communication link, the wireless signal being indicative of at least one command for causing an action to be performed by the locomotive;
 - c) said slave controller being responsive to the wireless signal to generate control signals for transmission to the controller module to implement the at least one command;
 - d) said slave controller being operative to receive over a second communication link, ~~different from the first communication link,~~ an identifier of said transmitter, the second communication link being a wireless communication link;
 - e) said slave controller being operative to output over the second communication link an identifier of said slave controller for transmission to said transmitter;
 - f) the wireless signal including data derived from the identifier of said transmitter.
86. (Previously Presented) A remote control system as defined in claim 85, wherein said transmitter includes a data storage for storing the identifier of said slave controller.
87. (Previously Presented) A remote control system as defined in claim 86, wherein said data storage is operative to store the identifier of said transmitter.
88. (Previously Presented) A remote control system as defined in claim 87, wherein said transmitter includes a signal transmitting unit for transmitting the wireless signal over the first communication link.
89. (Currently Amended) A remote control system as defined in claim 88, wherein said transmitter includes a message builder in communication with said data storage, said message builder operative to construct a message having a tag portion and a command portion, the tag portion conveying data derived from the identifier of said slave controller

and data derived from the identifier of said transmitter, the command portion conveying the ~~at least one~~ command.

90. (Currently Amended) A remote control system as defined in claim 89, wherein said transmitter has an interface in communication with said data storage for outputting the identifier of said transmitter over ~~a communication link different from said first communication link~~ the second communication link.
91. (Previously Presented) A remote control system as defined in claim 90, wherein said interface is operative to receive the identifier of said slave controller and to transmit the identifier of said slave controller to said data storage for storage therein.
92. (Previously Presented) A remote control system as defined in claim 91, wherein said interface is an IR interface.
93. (Currently Amended) A remote control system as defined in claim 89, wherein the ~~at least one~~ action to be performed by the locomotive is acceleration.
94. (Currently Amended) A remote control system as defined in claim 89, wherein the ~~at least one~~ action to be performed by the locomotive is braking.
95. (Previously Presented) A remote control system as defined in claim 85, wherein said slave controller includes:
- a) a data storage for holding the identifier of said slave controller;
 - b) an interface in communication with said data storage, said interface operative to output over the second communication link via said interface the identifier of said slave controller.
96. (Previously Presented) A remote control system as defined in claim 95, wherein said interface is operative to receive over the second communication link the identifier of said transmitter and to direct the identifier of said transmitter to said data storage for storage therein.

97. (Previously Presented) A remote control system as defined in claim 96, wherein the wireless signal transmitted by said transmitter over the first communication link conveys a message including:
- a) a command portion indicative of the at least one command;
 - b) a tag portion including data derived from the identifier of said transmitter and data derived from the identifier of said slave controller.
98. (Currently Amended) A remote control system as defined in claim 97, wherein said slave controller includes a signal receiver unit for receiving the wireless signal transmitted by said transmitter over the first communication link.
99. (Previously Presented) A remote control system as defined in claim 98, wherein said slave controller includes a logical processing unit in communication with said data storage and with said signal receiver unit, said logical processing unit being operative to:
- a) perform a validation procedure on the message including comparing data in the tag portion in the message with the identifier of said transmitter and the identifier of said slave controller in the data storage;
 - b) if the validation procedure validates the message generating control signals for transmission to the controller module for causing the locomotive to perform the at least one action.
100. – 103. (Cancelled)
104. (Currently Amended) A method for remotely controlling a locomotive in which is mounted a slave controller, said method comprising:
- a) providing a portable transmitter;
 - b) communicating to the portable transmitter an identifier of the slave controller over a first communication link, the first communication link being a wireless communication link;

- c) storing in a data storage in said portable transmitter ~~the identifier of the portable transmitter and the~~ identifier of the slave controller communicated over the first communication link;
- d) outputting from the portable transmitter over the first communication link ~~the~~ an identifier of the portable transmitter for transmission to the slave controller;
- e) transmitting to the slave controller a wireless signal over a second communication link ~~different from the first communication link~~, the second communication link being an RF communication link, the wireless signal conveys a message including:
 - i) a command portion indicative of at least one command for causing an action to be performed by the locomotive;
 - ii) a tag portion including ~~the data derived from the identifier of the portable transmitter stored in the data storage and data derived from the identifier of the slave controller stored in the data storage.~~

105. (Previously Presented) A method as defined in claim 104, wherein the first communication link is an IR link.

106. (Currently Amended) A method for remotely controlling a locomotive in which is provided a controller module, comprising:

- a) mounting on board the locomotive a slave controller;
- b) interfacing the slave controller with the controller module;
- c) communicating to the slave controller over a first communication link an identifier of a remote portable transmitter, the first communication link being a wireless communication link;
- d) storing in a data storage in the slave controller the identifier of the remote portable transmitter;
- ~~e) storing in the data storage an identifier of the slave controller;~~
- ~~f) e)~~ transmitting from the remote portable transmitter a wireless signal over a second communication link different from the first communication link, the second

communication link being an RF communication link, the wireless signal conveying a message including:

- i) a command portion indicative of at least one command for causing an action to be performed by the locomotive; and
- ii) a tag portion;

~~g)f)~~ receiving the wireless signal at the slave controller;

~~h)g)~~ performing a validation procedure at the slave controller by comparing data in the tag portion of the message in the received wireless signal with the identifier of the remote portable transmitter in the data storage and ~~the an~~ identifier of the slave controller ~~in the data storage~~;

~~i)h)~~ if the validation procedure validates the message in the received wireless signal, generating control signals and directing the control signals to the controller module for causing the locomotive to perform the ~~at least one~~ action.

107. (Currently Amended) A device for synchronizing addresses in a communication control system, the communication control system including a first component having a memory storing a first identifier and a second component having a memory storing a second identifier, said device comprising:

- a) a port for establishing a communication link with the first component and for establishing a communication link with the second component, the communication link with one of the first and second components being a wireless communication link;
- b) a memory unit;
- c) a processing unit operatively coupled to said port and said memory unit, said processing unit being suitable for:
 - i) establishing a communication link through said port with the first component for acquiring the first identifier from the first component;
 - ii) storing the first identifier in said memory unit;

- iii) establishing a communication link through said port with the second component for transmitting the first identifier stored in said memory unit to the second component, ~~such as to allow the second component to hold the first identifier and the second identifier in a storage unit at the second component.~~
108. (Currently Amended) A device as defined in claim 107, wherein the first component is a slave controller module for controlling a locomotive and the second component is a transmitter unit.
109. (Currently Amended) A device as defined in claim 107, wherein the first component is a transmitter unit and the second component is a slave controller module for controlling a locomotive.
110. (Previously Presented) A device as defined in claim 107, wherein said port has a first interface for communication with the first component and a second interface for communication with the second component.
111. (Cancelled)
112. (Currently Amended) A device as defined in claim ~~111~~ 110, wherein at least one of said first interface and said second interface ~~suitable for wireless data communication~~ is an infrared interface.
113. (Currently Amended) A device as defined in claim 110, wherein at least one of said first interface and said second interface is ~~suitable for~~ a serial connection interface.
114. (Currently Amended) A device as defined in claim 107, wherein said processing unit is further suitable for:
- a) establishing a communication link with the second component for acquiring the second identifier from the second component;

- b) storing the second identifier in said memory unit;
 - c) establishing a communication link with the first component for transmitting the second identifier stored in said memory unit to the first component, ~~such as to allow the first component to hold the first identifier and the second identifier in a storage unit at the first component.~~
115. (Currently Amended) A method for synchronizing addresses in a communication control system, the communication control system having a first component associated to a first identifier, a second component associated to a second identifier and an operator programming unit, said method comprising:
- i) establishing a communication link between the operator programming unit and the first component for transmitting the first identifier from the first component to the operator programming unit;
 - ii) establishing a communication link between the operator programming unit and the second component for transmitting the first identifier from the operator programming unit to the second component, wherein the communication link between the operator programming unit and one of the first component and the second component is a wireless communication link;
 - iii) generating an address at the second component on the basis of the first identifier and the second identifier.
116. (Previously Presented) A method as defined in claim 115, wherein the first component is a slave controller module and the second component is a transmitter unit.
117. (Previously Presented) A method as defined in claim 115, wherein the first component is a transmitter unit and the second component is a slave controller module.
118. (Cancelled)

119. (Currently Amended) A method as defined in claim ~~118~~ 115, wherein said wireless communication link is an infrared communication link.
120. (Currently Amended) A method as defined in claim ~~115~~, wherein said ~~the~~ communication link between the operator programming unit and ~~at least one of the first component and the second component~~ is a serial communication link.
121. (Previously Presented) A method as defined in claim 115, wherein said method further comprises:
- i) establishing a communication link with the second component for acquiring the second identifier from the second component;
 - ii) establishing a communication link with the first component for transmitting the second identifier to the first component;
 - iii) generating an address at the first component on the basis of the second identifier and the first identifier.
122. (Currently Amended) A computer readable storage medium including a program element suitable for execution by a computing apparatus for synchronizing addresses in a communication control system, the communication control system having a first component associated to a first identifier and a second component associated to a second identifier, the computing apparatus comprising:
- a) a memory unit;
 - b) a processing unit for executing said program element, said processing unit in an operative relationship with said memory unit, said processing unit being suitable for when said program element is executed by said processing unit, said program element causing:
 - ~~i) implementing a port for establishing a communication link with the first component and a communication link with the second component;~~
 - ii) i) establishing establishment of a communication link through said port between the computing apparatus with and the first component for acquiring the first identifier from the first component;

~~iii)ii)~~ ~~storing-storage of~~ the first identifier in said memory unit;

~~iv)iii)~~ ~~establishing-establishment of a communication link through the port with~~
~~between the computing apparatus and the second component for~~
~~transmitting the first identifier stored in said memory unit to the second~~
~~component, thereby allowing the second component to hold the first~~
~~identifier and the second identifier in a storage unit at the second~~
~~component, the communication link between the computing apparatus and~~
~~one of the first and second components being a wireless communication~~
~~link.~~

123. (Currently Amended) A computer readable storage medium as defined in claim 122, wherein the first component is a slave controller module for controlling a locomotive and the second component is a transmitter unit.

124. (Currently Amended) A computer readable storage medium as defined in claim 122, wherein the first component is a transmitter unit and the second component is a slave controller module for controlling a locomotive.

125. (Cancelled)

126. (Cancelled)

127. (Currently Amended) A computer readable storage medium as defined in claim ~~126~~122, wherein ~~at least one of said first interface and said second interface suitable for wireless data communication is an infrared interface~~ the wireless communication link is an infrared communication link.

128. (Cancelled)

129. (Currently Amended) A computer readable storage medium as defined in claim 122, wherein when said program element is executed by said processing unit is further suitable for said program element causing:

- i) ~~establishing establishment of a communication link through the port with~~between the computing apparatus and ~~the second component for~~ acquiring the second identifier from the second component;
- ii) ~~storing~~storage of the second identifier in said memory unit;
- iii) ~~establishing establishment of a communication link through the port with~~between the computing apparatus and the first component for transmitting the second identifier stored in said memory unit to the first component, ~~thereby allowing the first component to hold the first identifier and the second identifier in a storage unit at the first component.~~

130. (Currently Amended) A communication control system comprising:

- a) a first component having a memory storing a first identifier;
- b) a second component having a memory storing a second identifier;
- c) a device for synchronizing addresses between said first component and said second component, said device comprising:
 - i) a port for establishing a communication link with said first component and a communication link with said second component;
 - ii) a memory unit;
 - iii) a processing unit operatively coupled to said port and said memory unit, said processing unit being suitable for:
 - (1) establishing a communication link through said port with said first component for acquiring the first identifier from the first component;
 - (2) storing the first identifier in said memory unit;
 - (3) establishing a communication link through said port with said second component for transmitting the first identifier stored in said memory unit to said second component, such as to allow said second component to hold the first identifier and the second identifier in a storage unit at said second component;

- d) said second component being operative for generating an address on the basis of the first identifier and the second identifier, wherein the communication link with one of said first component and said second component is a wireless communication link.
131. (Currently Amended) A control system as defined in claim 130, wherein said first component is a slave controller module for a locomotive and said second component is a transmitter unit.
132. (Currently Amended) A control system as defined in claim 130, wherein said first component is a transmitter unit and said second component is a slave controller module for a locomotive.
133. (Previously Presented) A control system as defined in claim 130, wherein said port has a first interface for communication with said first component and a second interface for communication with said second component.
134. (Cancelled)
135. (Currently Amended) A control system as defined in claim ~~134~~133, wherein at least one of said first interface and said second interface ~~suitable for wireless data communication~~ is an infrared interface.
136. (Cancelled)
137. (Previously Presented) A control system as defined in claim 130, wherein said processing unit is further suitable for:
- i) establishing a communication link through said port with said second component for acquiring the second identifier from said second component;
 - ii) storing the second identifier in said memory unit;

- iii) establishing a communication link through said port with said first component for transmitting the second identifier stored in said memory unit to said first component, such as to allow said first component to hold the first identifier and the second identifier in a storage unit at the first component.

138. (Previously Presented) A transmitter for remotely controlling a locomotive in which is mounted a slave controller, said transmitter comprising:

- a) an interface for receiving an identifier of the slave controller via a first wireless communication link;
- b) a signal transmitting unit for transmitting a modulated signal over a second communication link, the second communication link being an RF communication link, the modulated signal being indicative of at least one command for causing an action to be performed by the locomotive, the modulated signal conveying data derived from the identifier of the slave controller received over the first communication link, said signal transmitting unit including a modulator outputting the modulated signal.

139. (Previously Presented) A transmitter as defined in claim 138, comprising a data storage in communication with said interface for storing the identifier of the slave controller received via the first communication link.

140. (Previously Presented) A transmitter as defined in claim 139, wherein said data storage is operative to store an identifier of said transmitter.

141. (Previously Presented) A transmitter as defined in claim 140, wherein said transmitter includes a message builder in communication with said data storage, said message builder being operative to construct a message having a tag portion and a command portion, the tag portion conveying data derived from the identifier of the slave

controller and data derived from the identifier of said transmitter, the command portion conveying the at least one command.

142. (Previously Presented) A transmitter as defined in claim 141, including a message encoder in communication with said message builder to encode the message constructed by said message builder.
143. (Previously Presented) A transmitter as defined in claim 142, wherein said message encoder processes the message constructed by said message builder to reduce an occurrence of consecutive 0's or 1's in the message constructed by said message builder.
144. (Previously Presented) A transmitter as defined in claim 142, wherein said signal transmitting unit is in communication with said message encoder for receiving the message encoded by said message encoder and for producing the modulated signal conveying the at least one command on the basis of the message encoded by said message encoder.
145. (Currently Amended) A transmitter for remotely controlling a locomotive, said transmitter comprising:
- a) a data storage for holding an identifier of said transmitter;
 - b) an interface in communication with said data storage, said interface being operative to establish a first communication link with an external entity for transmitting to the external entity data derived from the identifier of said transmitter via the first communication link, said first communication link being a wireless communication link;
 - c) a signal transmitting unit in communication with said data storage, said signal transmitting unit being operative to transmit a modulated signal over a second communication link, the second communication link being an RF communication link, the modulated signal conveying:
 - i) at least one command for causing an action to be performed by the locomotive; and
 - ii) data derived from the identifier of said transmitter;
 - d) said signal transmitting unit including a modulator releasing the modulated signal.

146. (Previously Presented) A transmitter as defined in claim 145, wherein said signal transmitting unit is operative to transmit the modulated signal to a slave controller mounted on board the locomotive, said data storage being operative to store an identifier of the slave controller.
147. (Previously Presented) A transmitter as defined in claim 146, wherein said transmitter further comprises a message builder in communication with said data storage, said message builder being operative to construct a message having a tag portion and a command portion, the tag portion conveying data derived from the identifier of the slave controller and data derived from the identifier of said transmitter, the command portion conveying the at least one command.
148. (Previously Presented) A transmitter as defined in claim 147, including a message encoder in communication with said message builder to encode the message constructed by said message builder.
149. (Previously Presented) A transmitter as defined in claim 148, wherein said signal transmitting unit is in communication with said message encoder for receiving the message encoded by said message encoder and for producing the modulated signal conveying the at least one command on the basis of the message encoded by said message encoder.
150. (Previously Presented) A transmitter as defined in claim 148, wherein said message encoder processes the message constructed by said message builder to reduce an occurrence of consecutive 0's or 1's in the message constructed by said message builder.
151. (Previously Presented) A transmitter as defined in claim 149, wherein said modulator modulates the message encoded by said message encoder to produce the modulated signal conveying the at least one command.

152. (Previously Presented) A transmitter as defined in claim 145, wherein said interface is operative to receive over the first communication link the identifier of the slave controller for storage in said data storage.
153. (Previously Presented) A transmitter as defined in claim 145, wherein the first communication link is an IR communication link.
154. (Previously Presented) A transmitter as defined in claim 145, wherein the action to be performed by the locomotive is acceleration.
155. (Previously Presented) A transmitter as defined in claim 145, wherein the action to be performed by the locomotive is braking.
156. (Previously Presented) A transmitter as defined in claim 139, wherein said first communication link is an IR link.
157. (Previously Presented) A transmitter as defined in claim 139, wherein the action to be performed by the locomotive is acceleration.
158. (Previously Presented) A transmitter as defined in claim 139, wherein the action to be performed by the locomotive is braking.
159. (New) A transmitter as defined in claim 32, wherein the at least one command includes command information derived from the command portion of the message.
160. (New) A transmitter as defined in claim 44, wherein the at least one command includes command information derived from the command portion of the message.
161. (New) A transmitter as defined in claim 30, wherein the first communication link is an IR communication link.
162. (New) A transmitter as defined in claim 43, wherein the first communication link is an IR communication link.
163. (New) A slave controller as defined in claim 53, wherein the first communication link is an IR communication link.

164. (New) A combination as defined in claim 63, wherein the first communication link is an IR communication link.